



A VIDEODSP™ product, the VIEW Pro D310 Decoder supports distribution of all digital media via existing IP networks and infrastructure to single-image, full-screen video applications, at an unrivaled cost advantage, meeting and exceeding all of your essential Network Media Streaming needs.

AV over IP streaming and delivery with unmatched scalability and ease of deployment has never been more accessible.

### Ultra High-Quality Video

- + High profile H.264 lossless compression
- + Full HD 1080p60 resolution
- + 4:2:0 color space

### Standards-based

- + Existing IP network infrastructure
- + Uses standard CAT 5e/6 cabling

### Flexible Control

- + VIEW Virtual Matrix control application
- + Matrix view of all live sources & destinations
- + In-room controller - touch panel & web
- + 3<sup>rd</sup> party control: AMX, Crestron, Utelogy

### Configuration & Management

- + Auto-discovery of encoders & decoders
- + Device configuration & management
- + Project management
- + System monitoring & troubleshooting



#### APPLICATIONS

Corporate

---

Education

---

Command & Control Centers

---

Telemedicine & Healthcare

---

Hospitality & Entertainment

---

Transportation

---

Houses of Worship

D310



### PRODUCT SPECIFICATIONS

#### Video

##### Digital Video Connection:

HDMI 1.4a output

##### Supported Resolutions:

1080p60 1920×1080  
HD720 1280×720  
UXGA 1600×1200  
WSXGA+ 1680×1050  
SXGA+ 1440×1080 & 1440×1050  
WXGA 1440×900  
SXGA 1280×1024  
XGA 1024×768  
SVGA 800×600  
VGA 640×480

##### Compression Standard:

H.264/MPEG4 Part 10 (AVC)  
Baseline, Main, High profiles up to 4.2

##### Color Space Support:

YCbCr 4:2:0

#### Audio

HDMI

S/PDIF

USB (future)

#### Networking

10/100/1000 Mbps RJ45 (Gigabit)

#### General

##### Power:

External Power Supply - AC 100-240V input, DC 5V/2A power output

#### Mechanical

##### Dimensions (W x H x D):

0.88" × 4.5" × 4.5" (22mm × 114mm × 114mm)

##### Mounting:

VESA mounting bracket (supports 75mm × 75mm and 100mm × 100mm)

##### Operating Temperature:

32 to 104 °F (0 to 40 °C)

##### Items Included:

Power supply  
VESA mounting bracket  
USB to DB9 serial adapter

#### Part Number

910-0003-002

#### Other VIEW Pro Products

VIEW Pro Encoder E120: 910-0000-001

VIEW Pro Encoder E110: 910-0000-006

VIEW Pro Decoder D110: 910-0001-001

VIEW Pro Decoder D210: 910-0003-001

## SALES AND INQUIRIES

#### Headquarters

5225 Wiley Post Way,  
Suite 500  
Salt Lake City, UT 84116

#### US & Canada

Tel: 801.975.7200  
TollFree: 800.945.7730  
Fax: 801.303.5711

#### International

Tel: +1.801.975.7200  
global@clearone.com

#### Sales

Tel: 801.975.7200  
sales@clearone.com

#### TechSales

Tel: 801.974.3760  
techsales@clearone.com

#### TechSupport

Tel: 801.974.3760  
tech.support@clearone.com