

**ClearOne® Aura™**  
Quick-Start Guide



**UNITE® 20 PRO WEBCAM**  
VIDEO SOLUTION

# UNITE 20 Pro Webcam

## CONTACT INFORMATION

### Headquarters

5225 Wiley Post Way  
Suite 500  
Salt Lake City, UT 84116  
US: +1.801.975.7200  
International: +1.801.975.7200

### Aura Sales

US: +1.888.HEY.AURA  
International: +1.801.975.7200  
aurasales@clearone.com

### Aura Tech Support


US: +1.888.HEY.AURA  
International: +1.801.975.7200  
auratechsupport@clearone.com

© 2021 ClearOne, Inc. All rights reserved.

Information in this document is subject to change without notice.

Document: QSG-0094-002v1.1 February 2021

## COMPONENTS INCLUDED

 A line drawing of a webcam. It has a rectangular body with a lens in the center, a small microphone grille on the left, and a small square button on the right. A USB cable is attached to the back of the device. The webcam is mounted on a small, rectangular base.	<p>AUR-2100-006 UNITE 20 Pro Webcam</p>
--	---

### SAFETY PRECAUTIONS

#### Careful transportation

Transport, store, and install the camera to prevent heavy pressure, violent vibration, or immersion of the camera. The shell of the camera is an organic material. Avoid contact with any material that may cause corrosion to the shell.

#### Careful installation

Install the camera on a smooth desktop or on the top of a computer monitor.

#### Do not disassemble

Damage caused by the user's disassembly is not covered by warranty.

Electromagnetic fields at specific frequencies may affect the camera's image.

### PRODUCT FEATURES

#### 1080P Full HD Super Wide Angle

Supports 1080P HD, providing up to 1080@30 fps/25 fps image encoding output, while being backward compatible with 720p resolution. Wide field of view, horizontal field of view up to 120 °.

### **USB 2.0**

Full-featured USB 2.0 interface, power supply, video, audio in one, can also support 2-channel USB video signal source + 1 audio source.

### **Built-in Microphone**

Built-in microphone array, omnidirectional pickup, up to 3 meters pickup distance, unique noise suppression algorithm, make your voice perfect presentation.

### **Low Illumination**

The new CMOS image sensor with super-high noise-to-noise ratio at star level can effectively reduce image noise under low illumination conditions. At the same time, 2D and 3D noise reduction algorithms are applied, greatly reducing image noise, and maintaining the picture even under ultra-low illumination conditions. Clean and clear, image signal to noise ratio of up to 55 dB or more.

### **Easy Installation**

Standard with a damped rotating shaft bracket, adapted to almost 100% of displays on the market, easy to install, stable and reliable

## UNITE 20 Pro Webcam

### INSTALLATION AND USE

1. Use the camera in stable lighting conditions.
2. Avoid use in or near facilities that transmit high-power radio waves, such as television stations or radio-transmitting station.
3. Avoid particularly bright objects, such as sunlight, lights, etc.
4. For monitors with a thickness of 170 mm or less, you can mount the camera on the top of the monitor.
5. With a USB cable, connect the USB 2.0 connector on the back of the camera to a USB connector on your personal computer.