

ClearOne Aura™

With **Aura**,
Professionals can
now **Re-imagine**
their **Workspaces**
at **Home**



UNITE® 150 PTZ Camera



Professional-grade HD USB PTZ camera for your professional home office with 1080p video, 12x optical zoom, and wide-angle video capture with advanced noise reduction.

Aura Professional Home Office Solution

Dramatically enhances the audio and video experience for any **cloud-based collaboration** application for your **professional home office**

COMPATIBLE WITH




Enhance Your Cloud Collaboration

Highlights

- † Full-HD 1080p30 video and 12x optical zoom for high video quality, regardless of where the camera is installed in your professional home office.
- † Control the camera's functions via IR remote, RS-232, or UVC protocol.
- † Super-high SNR with advanced 2D and 3D noise reduction.
- † Simple USB 3.0/2.0 compatibility with UVC and UAC protocol support.
- † Compatible with popular applications such as COLLABORATE® Space, Microsoft® Teams, WebEx™ Zoom™, Google® Meet™, and more.
- † FREE COLLABORATE® Space lifetime subscription — ClearOne's high quality, award winning cloud-based video collaboration application.
- † Transforms any meeting room into a professional-grade video collaboration room.

Aura Professional Home Office Application

Complete your **UNITE® 150 PTZ Camera** setup by adding other ClearOne Aura products



Specifications

- + AUR-2100-104 UNITE® 150 USB PTZ Camera

INCLUDES

- + Free COLLABORATE® Space lifetime subscription

VIDEO

- + VIDEO FORMATS: 1080p30, 1080p25, 720p30, 720p25
- + Sensor: 1/2.7 inch, CMOS
- + Effective pixel: 2.07M
- + Scanning mode: Progressive
- + Lens : 12x, f3.5 mm – 42.3 mm, f1.8 – f2.8
- + Minimal illumination: 0.5 lux @ (f1.8, AGC ON)
- + Shutter: 1/30 S – 1/10000 S
- + White balance: Auto , Indoor, Outdoor, One Push, Manual
- + Backlight compensation: Supported
- + Digital Noise Reduction: 2D & 3D
- + Video S/N: ≥55dB
- + Horizontal angle of view: 72.5° – 6.9°
- + Vertical angle of view: 44.8° – 3.9°
- + Horizontal rotation range: ±170°
- + Vertical rotation range: -30° – +90°
- + Pan speed range: 1.7° – 100°/S
- + Tilt speed range: 1.7° – 69.9°/S
- + H & V FLIP: Supported
- + Image freezing: Supported
- + Number of presets: 255
- + Installation: Stand Mount, upside-down mount

INPUT/OUTPUT INTERFACE

- + Audio interface: 1-CH 3.5MM Audio Interface, Line In
- + USB interface: 1 x USB3.0: type B Female jack
- + Communication: 1 x Rs-232 in : 8-Pin Min din, Max distance: 30 m, Protocols: VISCA/Pelco-D/Pelco-P
- + 1x RS-232 Out: 8-Pin Min din, Max distance: 30 M, Protocols: visca network use Only

COMPATIBILITY

- + Operating Systems: Windows 7, Windows 8, Windows 8.1, Windows 10, MAC OS, Linux
- + Color System: YUV 4:2:2
- + USB 2.0: 720P30 maximum
- + NOTE: Use of USB 2.0 downgrades video quality. ClearOne does not recommend using USB 2.0 extenders.
- + USB Video Communication: UVC 1.0 - UVC 1.5
- + Audio on USB: Supported
- + UVC PTZ: Supported

POWER

- + Power jack: JEITA type (DC In 12 V)
- + Input voltage: DC 12 V
- + Current consumption: 1.0 A (max)
- + Power consumption: 12 W (max)

ENVIRONMENTAL

- + Operating temperature: +14° F–104° F (-10° C–40° C)
- + Storage temperature: -40° F–140° F (-40° C–60° C)
- + MTBF: >30000h

MECHANICAL

- + Dimensions (W x D x H): 5.67 x 5.67 x 6.61” (144 x 144 x 168mm)
- + Weight: 2.0lb (0.91kg)

OPTIONAL ACCESSORIES

- + AUR-2100-104 Wall Mount for UNITE® 150 Camera
- + AUR-2100-204 Ceiling Mount for UNITE® 150 Camera
- + 910-3200-702-30 USB 3.0 cable

Sales & Inquiries

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

Headquarters

US: +1.801.975.7200
International: +1.801.975.7200

Aura Sales

US: +1.888.HEY.AURA
International: +1.801.975.7200
aurasales@clearone.com

Aura Tech Support

US: +1.888.HEY.AURA
International: +1.801.975.7200
auratechsupport@clearone.com